Safety Data Sheet

SECTION 1: Product and company identification

Product name : Golfer's Lift Off Cleaner

Use of the substance/mixture : Cleaner

Product code

Company : Charter Products Co. 111 Gateway Road

Bensenville, IL 60106 - USA

T (630)616-1922

Emergency number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





:02 GH

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol Causes serious eye irritation

: Keep away from heat, hot surfaces, open flames, sparks. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Wash thoroughly after handling Wear eye protection, face protection

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

Precautionary statements (GHS-US)

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)	
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280	
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	(CAS No) 112-34-5	2.5 - 10	Eye Irrit. 2A, H319	
Alcohol Ethoxylate	(CAS No) 68439-46-3	1 - 2.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319	
propane	(CAS No) 74-98-6	1 - 2.5	Flam. Gas 1, H220 Compressed gas, H280	

 Date of issue: 11/25/2019
 Revision date: 06/01/2015
 Version: 1.0
 P GHS SDS
 Page 1 of 7

Safety Data Sheet

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). Ensure that medical

personnel are aware of the material(s) involved, and take precautions to protect themselves.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with

water/shower. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth with water.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes serious eye irritation.
Symptoms/injuries after inhalation : None under normal use.

Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms/injuries after ingestion : Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Keep watching the victim. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustion produces irritating gases. Extremely flammable aerosol.

Explosion hazard : Contents under pressure. Pressurized container: may burst if heated.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Move containers away from the fire area if this can

be done without risk. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire

burn out. In case of fire and/or explosion do not breathe fumes.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No flames, No sparks. Eliminate all sources of ignition. Evacuate unnecessary personnel. Stay

upwind/keep distance from source. Gas is denser than air. May accumulate in low areas e.g. close

to the ground.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

Emergency procedures : Avoid contact with skin, eyes and clothing. Evacuate unnecessary personnel. Keep upwind. Ventilate

spillage area. DO NOT touch spilled material. Do not breathe gas. Advice local authorities if

considered necessary.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Keep combustibles (wood, paper, oil,

etc.) away from spilled material. Move the cylinder to a safe and open area if the leak is irreparable.

Date of issue: 11/25/2019 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 2 of 7

Safety Data Sheet

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation. Following product recovery, flush area with water.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or

defective.

Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Do not spray on a naked flame or any incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. . Ground/bond container and receiving equipment. Do not re-use empty containers. Use only outdoors or in a well-ventilated area. Observe normal hygiene standards.

Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Pressurized container. Do not puncture, incinerate or crush.

Take precautionary measures against static discharge.

Storage conditions : Keep container closed when not in use. Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/122 °F. Refrigerate.

Incompatible products : Strong oxidizing agents.
Incompatible materials : Heat sources. Open flame.

Storage area : Meet the legal requirements. Store in a cool area. Store in a dry area.

Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
ACGIH	ACGIH STEL (ppm)	1000 ppm	
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)			
ACGIH	ACGIH TWA (ppm)	10 ppm	
propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	

8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. . If exposure limits have not been established, maintain airborne levels to an acceptable level. . Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective clothing.



Hand protection

: Gloves.

Eye protection

Chemical goggles or safety glasses.

Respiratory protection

: If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an airsupplied respirator.

Thermal hazard protection

: Use appropriate personal protective equipment when risk assessment indicates this is necessary.

Date of issue: 11/25/2019 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 3 of 7

Safety Data Sheet

Consumer exposure controls

: When using do not smoke. Use good personal hygiene practices. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Take off contaminated clothing and wash before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Cloudy. Aerosol. Colorless to pale yellow liquid.

Odor : mint-like

Odor threshold : No data available
pH : 10.3 - 11.3 Estimated
Melting point : No data available
Freezing point : No data available
Boiling point : 212 °F Estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available Explosive properties No data available Oxidizing properties : No data available Vapor pressure : No data available Relative density : No data available Relative vapor density at 20 °C : No data available

Specific gravity / density : 0.958 - 1.058 g/ml estimated

Solubility : No data available Log Pow : No data available Log Kow : No data available : No data available Auto-ignition temperature Decomposition temperature No data available No data available Viscosity : No data available Viscosity, kinematic Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

 Date of issue: 11/25/2019
 Revision date: 06/01/2015
 Version: 1.0
 P GHS SDS
 Page 4 of 7

Safety Data Sheet

Alcohol Ethoxylate (68439-46-3)		
LD50 oral rat	1400 mg/kg Estimated	
LD50 dermal rabbit	> 5000 mg/kg	
ATE CLP (oral)	1400.000 mg/kg body weight	

Skin corrosion/irritation : Not classified

pH: 10.3 - 11.3 Estimated

Serious eye damage/irritation Causes serious eye irritation.

pH: 10.3 - 11.3 Estimated

Respiratory or skin sensitization Not classified Not classified Germ cell mutagenicity Carcinogenicity Not classified Reproductive toxicity Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated

exposure)

Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : None under normal use.

Symptoms/injuries after skin contact Contact during a long period may cause light irritation.

Symptoms/injuries after eye contact Causes serious eye irritation. Symptoms/injuries after ingestion : Gastrointestinal complaints.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Collect and reclaim or dispose in sealed containers at licensed waste disposal site. . Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with local/regional/national regulations.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Handle unclean empty containers as full ones. This material and its container must be disposed of Additional information

in a safe manner. Do not re-use empty containers.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport hazard class(es) (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols

> flammable, (each not exceeding 1 L capacity) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102)

Date of issue: 11/25/2019 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 5 of 7

Safety Data Sheet

DOT Packaging Exceptions (49 CFR

173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft : 150 kg

only (49 CFR 175.75)

: A

: 306

: 75 kg

DOT Vessel Stowage Location

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950 Proper Shipping Name (IMDG) : Aerosols

Class (IMDG) : 2.1 - Flammable gases

Air transport

: UN1950 UN-No.(IATA)

Proper Shipping Name (IATA) : Aerosols, flammable Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

butane (106-97-8)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		
propane (74-98-6)		
Not listed on SARA Section 313 (Specific toxic chemical listings)		

California Proposition 65 - This product does not contain substances known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation


Date of issue: 11/25/2019 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 6 of 7

Safety Data Sheet

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 11/25/2019
 Revision date: 06/01/2015
 Version: 1.0
 P GHS SDS
 Page 7 of 7